# FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO Enterprise Products Operating LLC

AUTHORIZING THE OPERATION OF

Enterprise East

East Storage Splitter III Facility and East Product Handling Terminal

Other Warehousing and Storage

#### **LOCATED AT**

Chambers County, Texas
Latitude 29° 50′ 21″ Longitude 94° 53′ 33″
Regulated Entity Number: RN102984911

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:	O4269	Issuance Date: _	
For the Co	nmmission		

# **Table of Contents**

Section	Page
General Terms and Conditions	3
Special Terms and Conditions:	3
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	
Additional Monitoring Requirements	
New Source Review Authorization Requirements	9
Compliance Requirements	10
Risk Management Plan	12
Protection of Stratospheric Ozone	12
Alternative Requirements	12
Permit Location	12
Permit Shield (30 TAC § 122.148)	12
Attachments	13
Applicable Requirements Summary	14
Additional Monitoring Requirements	35
Permit Shield	42
New Source Review Authorization References	47
Alternative Requirement	53
Appendix A	56
Acronym List	

#### **General Terms and Conditions**

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five-year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

#### **Special Terms and Conditions:**

#### Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- 1. Permit holder shall comply with the following requirements:
  - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
  - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
  - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
  - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

- E. Emission units subject to 40 CFR Part 63, Subpart ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.1090 which incorporates the 40 CFR Part 63 Subpart by reference.
- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
  - (i) Title 30 TAC § 101.302 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
  - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
  - (iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
  - (v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
  - (i) Title 30 TAC § 101.352 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
  - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
  - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
  - (v) Title 30 TAC § 101.359 (relating to Reporting)
  - (vi) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
  - (vii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- H. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
  - (i) Title 30 TAC § 101.392 (relating to Exemptions)
  - (ii) Title 30 TAC § 101.401 (relating to Level of Activity Certification)
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
  - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
  - B. Title 30 TAC § 101.3 (relating to Circumvention)

- C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
- D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
- E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
- F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
- G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
- H. Title 30 TAC § 101.221 (relating to Operational Requirements)
- I. Title 30 TAC § 101.222 (relating to Demonstrations)
- J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
  - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
    - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
    - (ii) Title 30 TAC § 111.111(a)(1)(E)
    - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
    - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
      - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
      - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to

24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.

- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

#### (5) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
- However, if visible emissions are present during the observation, (b) the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the

observation or monitoring was performed to demonstrate compliance with a different requirement.

- B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:
  - (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
  - (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
  - (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
    - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
    - (2) Records of all observations shall be maintained.
    - (3)Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
    - (4) Compliance Certification:
      - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
      - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation

on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- C. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- D. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
  - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
  - (ii) Sources with an effective stack height (h<sub>e</sub>) less than the standard effective stack height (H<sub>e</sub>), must reduce the allowable emission level by multiplying it by [h<sub>e</sub>/H<sub>e</sub>]<sup>2</sup> as required in 30 TAC § 111.151(b)
  - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- E. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
  - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
  - (ii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).
- 5. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
  - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
  - B. Title 40 CFR § 60.8 (relating to Performance Tests)
  - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
  - D. Title 40 CFR § 60.12 (relating to Circumvention)

- E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
- F. Title 40 CFR § 60.14 (relating to Modification)
- G. Title 40 CFR § 60.15 (relating to Reconstruction)
- H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 6. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 7. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

#### **Additional Monitoring Requirements**

8. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

#### **New Source Review Authorization Requirements**

- 9. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the permits by rule identified in the PBR Supplemental Tables in the application), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
  - A. Are incorporated by reference into this permit as applicable requirements
  - B. Shall be located with this operating permit
  - C. Are not eligible for a permit shield

- 10. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 11. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
- 12. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
  - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
  - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
  - C. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

#### **Compliance Requirements**

- 13. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 14. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
  - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
    - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
      - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
  - B. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
- 15. Use of Emission Credits to comply with applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:

- (i) Title 30 TAC Chapter 115
- (ii) Title 30 TAC Chapter 117
- (iii) Offsets for Title 30 TAC Chapter 116
- B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
  - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
  - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
  - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
  - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
  - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
- 16. Use of Discrete Emission Credits to comply with the applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) If applicable, offsets for Title 30 TAC Chapter 116
    - (iv) Temporarily exceed state NSR permit allowables
  - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
    - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
    - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
    - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
    - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

(v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

#### **Risk Management Plan**

17. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

#### **Protection of Stratospheric Ozone**

- 18. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
  - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

#### **Alternative Requirements**

19. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the TCEQ Executive Director, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

#### **Permit Location**

20. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

#### Permit Shield (30 TAC § 122.148)

21. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

#### **Attachments**

**Applicable Requirements Summary** 

**Additional Monitoring Requirements** 

**Permit Shield** 

**New Source Review Authorization References** 

**Alternative Requirement** 

Unit Summary	1!	5
Applicable Requirements Summary	18	8

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

# **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BRMGEN	SRIC ENGINES	N/A	R7303-03	30 TAC Chapter 117, Subchapter B	No changing attributes.
BRMGEN	SRIC ENGINES	SRIC ENGINES N/A		40 CFR Part 60, Subpart IIII	No changing attributes.
BRMGEN	SRIC ENGINES	N/A	63ZZZZ-03	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
CWT-1	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5767-01	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
FL-06	FLARES	N/A	111-111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-06	FLARES N/A		115-720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
FL-08	FLARES	N/A	111-111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-08	FLARES N/A		115-720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
FL-COLD	FLARES	N/A	111-111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-COLD	FLARES	N/A	115-720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
FW-1	SRIC ENGINES	N/A	R7303-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FW-1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
FW-2	SRIC ENGINES	N/A	R7303-02	30 TAC Chapter 117, Subchapter B	No changing attributes.
FW-2	SRIC ENGINES	N/A	60IIII-01	40 CFR Part 60, Subpart IIII	No changing attributes.
FW-2	SRIC ENGINES	N/A	63ZZZZ-02	40 CFR Part 63, Subpart	No changing attributes.

# **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				ZZZZ	
GRP-P/P	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	223A-PPIII, 223B- PPIII, 223C-PPIII	R5121-01	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-SPENTC	STORAGE TANKS/VESSELS	PP3-T-1003, PP3-T-3003	R5111-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
H-1401	PROCESS HEATERS/FURNACES	N/A	R7303-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
H-1402	PROCESS HEATERS/FURNACES	N/A	R7303-02	30 TAC Chapter 117, Subchapter B	No changing attributes.
H-2401	PROCESS N/A HEATERS/FURNACES		R7303-03	30 TAC Chapter 117, Subchapter B	No changing attributes.
H-3401	PROCESS N/A HEATERS/FURNACES		R7303-04	30 TAC Chapter 117, Subchapter B	No changing attributes.
H-3401	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Dc-01	40 CFR Part 60, Subpart Dc	No changing attributes.
HT15.003	PROCESS HEATERS/FURNACES	N/A	R7303-05	30 TAC Chapter 117, Subchapter B	No changing attributes.
HT15.003	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Dc-02	40 CFR Part 60, Subpart Dc	No changing attributes.
PHT-LOAD	T-LOAD LOADING/UNLOADING OPERATIONS		R115-112	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
REGEN-1	PROCESS HEATERS/FURNACES	N/A	R7303-06	30 TAC Chapter 117, Subchapter B	No changing attributes.
REGEN-1	BOILERS/STEAM	N/A	60Dc-03	40 CFR Part 60, Subpart Dc	No changing attributes.

# **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver	
	GENERATORS/STEAM GENERATING UNITS					

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BRMGEN	EU	R7303-03	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	§ 117.8140(a) § 117.8140(a)(3)	§ 117.340(j) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
BRMGEN	EU	60IIII-02	СО	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
BRMGEN	EU	601111-02	NMHC and NO <sub>X</sub>	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
BRMGEN	EU	601111-02	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
BRMGEN	EU	60IIII-02	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).			
BRMGEN	EU	63ZZZZ- 03	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
CWT-1	EU	R5767-01	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(b)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(b)(1) § 115.764(b)(2) § 115.764(b)(3) § 115.764(b)(4) § 115.764(b)(5) § 115.764(c) § 115.764(f) ** See Alternative Requirement	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(4) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) § 115.766(i)(1)	§ 115.766(i)(2)
FL-06	CD	111-111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						period. Non-excessive upset events are subject to the provisions under §101.222(b).			
FL-06	EP	115-720	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) [G]§ 115.725(l) § 115.725(l)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(j) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)
FL-08	CD	111-111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FL-08	EP	115-720	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(3) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) [G]§ 115.725(l) § 115.725(l) § 115.725(l)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(j) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)
FL-COLD	CD	111-111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-COLD	EP	115-720	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(2)	§ 115.725(n) § 115.726(a)(1)(B)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					\$ 115.725(d)(2) \$ 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii) § 115.725(d)(2)(B)(iiii)	through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) [G]§ 115.725(l) § 115.725(l)	§ 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
FW-1	EU	R7303-01	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month	§ 117.8140(a) § 117.8140(a)(3)	§ 117.340(j) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						average.			
FW-1	EU	63ZZZZ- 01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6603(a)- Table2d.4 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(i) § 63.6625(i) § 63.6640(f)(1) § 63.6640(f)(2)(i) § 63.6640(f)(4) § 63.6640(f)(4)(i)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at an area source, you must comply with the requirements as specified in Table 2d.4.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)- Table6.9.a.i § 63.6640(a)- Table6.9.a.ii	§ 63.6625(i) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(e) § 63.6650(f)
FW-2	EU	R7303-02	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
FW-2	EU	601111-01	NMHC and NO <sub>X</sub>	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a)	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(c) [G]§ 60.4211(f) § 60.4218	KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.			
FW-2	EU	60IIII-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
FW-2	EU	63ZZZZ- 02	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further	None	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements apply for such engines under this part.			
GRP-P/P	EP	R5121-01	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
GRP- SPENTC	EU	R5111-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
H-1401	EU	R7303-01	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(b) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
H-1401	EU	R7303-01	NO <sub>X</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(b) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(p)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-1402	EU	R7303-02	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-1402	EU	R7303-02	NO <sub>X</sub>	30 TAC Chapter	§ 117.310(d)(3)	An owner or operator may	[G]§ 117.335(a)(1)	§ 117.345(a)	§ 117.335(b)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				117, Subchapter B	§ 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	\$ 117.335(a)(4) \$ 117.335(b) \$ 117.335(d) \$ 117.335(e) \$ 117.335(g) \$ 117.340(a) \$ 117.340(p)(1) \$ 117.340(p)(2)(A) \$ 117.340(p)(2)(A) \$ 117.340(p)(2)(C) \$ 117.340(p)(2)(C) \$ 117.340(p)(2)(C) \$ 117.340(p)(2)(C) \$ 117.8000(c) \$ 117.8000(c)(1) \$ 117.8000(c)(3) \$ 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	\$ 117.335(g) \$ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) \$ 117.8010 [G]§ 117.8010(1) \$ 117.8010(2)(A) \$ 117.8010(2)(B) \$ 117.8010(2)(C) \$ 117.8010(2)(D) [G]§ 117.8010(3) \$ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-2401	EU	R7303-03	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(b) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(c) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-2401	EU	R7303-03	NO <sub>X</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	\$ 117.335(b) \$ 117.335(d) \$ 117.335(e) \$ 117.335(g) \$ 117.340(a) \$ 117.340(p)(1) \$ 117.340(p)(1) \$ 117.340(p)(2)(A) \$ 117.340(p)(2)(B) \$ 117.340(p)(2)(C) \$ 117.8000(c) \$ 117.8000(c) \$ 117.8000(c)(1) \$ 117.8000(c)(5) \$ 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(1) § 117.345(f)(9)	§ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-3401	EU	R7303-04	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-3401	EU	R7303-04	NO <sub>X</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) §	An owner or operator may not use the alternative methods specified in	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) § 117.345(f)(1)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.340(e)(4) § 117.340(p)(1) § 117.340(p)(1) § 117.340(p)(2) § 117.340(p)(3)	§§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(0)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.8000(c) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
H-3401	EU	60Dc-01	РМ	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
H-3401	EU	60Dc-01	PM (Opacity)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
H-3401	EU	60Dc-01	SO <sub>2</sub>	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HT15.003	EU	R7303-05	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
HT15.003	EU	R7303-05	NO <sub>X</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.340(e)(4) § 117.340(p)(1) § 117.340(p)(1) § 117.340(p)(3)	NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101,	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(p)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(2)(D) [G]§ 117.8010(4) [G]§ 117.8010(6) [G]§ 117.8010(6) [G]§ 117.8010(7)
HT15.003	EU	60Dc-02	PM	40 CFR Part 60,	§ 60.40c(a)	This subpart applies to each	None	§ 60.48c(g)(1)	[G]§ 60.48c(a)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Dc		steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).		§ 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	
HT15.003	EU	60Dc-02	PM (Opacity)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
HT15.003	EU	60Dc-02	SO <sub>2</sub>	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
PHT-LOAD	EU	R115-112	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(3) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Liquefied petroleum gas. All loading and unloading of liquefied petroleum gas is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
REGEN-1	EU	R7303-06	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) ** See Periodic Monitoring Summary		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
REGEN-1	EU	R7303-06	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) (8) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(4) § 117.340(e)(4) § 117.340(p)(1) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(b) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(A) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.340(p)(2)(C) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)
REGEN-1	EU	60Dc-03	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
REGEN-1	EU	60Dc-03	PM (Opacity)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						that has a maximum design heat input capacity of 2.9-29 megawatts (MW).			
REGEN-1	EU	60Dc-03	SO <sub>2</sub>	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)

Additi	ional Monitoring Requ	iirements	
Periodic Monitoring Summary			36

#### **Periodic Monitoring Summary**

Unit/Group/Process Information	
ID No.: H-1401	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 117, Subchapter B	SOP Index No.: R7303-01
Pollutant: CO	Main Standard: § 117.310(c)(1)
Monitoring Information	
Indicator: Fuel consumption	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: Maximum CO concentration shall not exceed 400 ppmv at 3.0% O2, dry	

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption

Any calculated emission rate above the maximum limit shall be considered and reported as a deviation.

Unit/Group/Process Information		
ID No.: H-1402		
Control Device ID No.: N/A	No.: N/A Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 117, Subchapter B	SOP Index No.: R7303-02	
Pollutant: CO	Main Standard: § 117.310(c)(1)	
Monitoring Information		
Indicator: Fuel consumption		
Minimum Frequency: Once per week		
Averaging Period: N/A		
Deviation Limit: Maximum CO concentration shall not exceed 400 ppmv at 3.0% O2, dry		

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption

Unit/Group/Process Information		
ID No.: H-2401		
Control Device ID No.: N/A	N/A Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 117, Subchapter B SOP Index No.: R7303-03		
Pollutant: CO	Main Standard: § 117.310(c)(1)	
Monitoring Information		
Indicator: Fuel consumption		
Minimum Frequency: Once per week		
Averaging Period: N/A		
Deviation Limit: Maximum CO concentration shall not exceed 400 ppmv at 3.0% O2, dry		

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other

written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption rate.

Unit/Group/Process Information		
ID No.: H-3401		
Control Device ID No.: N/A	/A Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 117, Subchapter B	SOP Index No.: R7303-04	
Pollutant: CO	Main Standard: § 117.310(c)(1)	
Monitoring Information		
Indicator: Fuel consumption		
Minimum Frequency: Once per week		
Averaging Period: N/A		
Deviation Limit: Maximum CO concentration shall n	ot exceed 400 ppmy at 3.0% O2. dry	

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption rate.

Unit/Group/Process Information		
ID No.: HT15.003		
Control Device ID No.: N/A	/A Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 117, Subchapter B	SOP Index No.: R7303-05	
Pollutant: CO	Main Standard: § 117.310(c)(1)	
Monitoring Information		
Indicator: Fuel consumption		
Minimum Frequency: Once per week		
Averaging Period: N/A		
Deviation Limit: Maximum CO concentration shall n	ot exceed 400 ppmy at 3.0% O2. dry	

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption rate.

Unit/Group/Process Information		
ID No.: REGEN-1		
Control Device ID No.: N/A	.: N/A Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 117, Subchapter B SOP Index No.: R7303-06		
Pollutant: CO	Main Standard: § 117.310(c)(1)	
Monitoring Information		
Indicator: Fuel consumption		
Minimum Frequency: Once per week		
Averaging Period: N/A		
Deviation Limit: Maximum CO concentration shall not exceed 400 ppmv at 3.0% O2, dry		

Periodic Monitoring Text: Measure and record fuel consumption. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with the manufacturer's specifications or other written procedures.

The fuel consumption rate shall be used in conjunction with AP-42 emission factors or most recent stack test to calculate the CO emission rate in lb/hr. The calculated CO emission rate shall be less than the deviation limit determined at the CO concentration limit of 400 ppmv and the maximum fuel consumption rate.

	Permit Shield	
Permit Shield		43

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
CWT-1	N/A	40 CFR Part 63, Subpart Q	Not operated with chromium-based water treatment chemicals.
EPHT-MCAP	N/A	40 CFR Part 60, Subpart Kb	These are pressure vessels with no emissions to the atmosphere.
GRP-CAUSTIC	PP3-T-1004, PP3-T-3004	30 TAC Chapter 115, Storage of VOCs	These vessels do not store volatile organic compounds.
GRP-CAUSTIC	PP3-T-1004, PP3-T-3004	40 CFR Part 60, Subpart Kb	These vessels do not store volatile organic liquids.
GRP-DEGAS	DEGAS-A, DEGAS-B, DEGAS-C, DEGAS-DE	30 TAC Chapter 115, HRVOC Vent Gas	Gaseous emissions to atmosphere are not emitted through stationary vents.
GRP-DEGAS	DEGAS-A, DEGAS-B, DEGAS-C, DEGAS-DE	30 TAC Chapter 115, Vent Gas Controls	Gaseous emissions to atmosphere are not emitted through stationary vents.
GRP-DIESEL	D-TANK-1, D-TANK-2, EQUIP-D- TANK	30 TAC Chapter 115, Storage of VOCs	Storage tanks with storage capacity less than or equal to 1,000 gallons.
GRP-DIESEL	D-TANK-1, D-TANK-2, EQUIP-D- TANK	40 CFR Part 60, Subpart Kb	Storage vessel capacity is less than 75 cubic meters (19,812 gallons).
GRP-FCTK	FTK-13E, FTK-20E, TK-DGS109, TK-FOA3	30 TAC Chapter 115, Storage of VOCs	The frac tanks do not meet the definition of a storage vessel.
GRP-FCTK	FTK-13E, FTK-20E, TK-DGS109, TK-FOA3	40 CFR Part 60, Subpart Kb	Storage vessel capacity is less than 75 cubic meters (19,812 gallons).
GRP-FWPOND	FWPOND-E, FWPOND-W	30 TAC Chapter 115, Industrial Wastewater	Not an affected VOC wastewater stream according to 115.140(2).
GRP-P/P	223A-PPIII, 223B-PPIII, 223C-PPIII	40 CFR Part 60, Subpart NNN	Does not produce chemicals listed in 60.667 as a product, co-product, or intermediate.
GRP-P/PFUG	F-100, F-3.01, F-3.02, F-3.03, F-	30 TAC Chapter 115, HRVOC Fugitive	Fugitives not associated with a synthetic organic

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
	BULLETTS, F-DEHY	Emissions	chemical, polymer, resin, or MTBE manufacturing process, or natural gas/gasoline processing operation as defined in §115.10.
GRP-P/PFUG	F-100, F-3.01, F-3.02, F-3.03, F-BULLETTS, F-DEHY	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Fugitives not associated with a synthetic organic chemical, polymer, resin, or MTBE manufacturing process, or natural gas/gasoline processing operation as defined in §115.10.
GRP-P/PFUG	F-100, F-3.01, F-3.02, F-3.03, F-BULLETTS, F-DEHY	40 CFR Part 60, Subpart KKK	Not an affected facility as defined in 60.630(a)(2) or (a)(3).
GRP-P/PFUG	F-100, F-3.01, F-3.02, F-3.03, F-BULLETTS, F-DEHY	40 CFR Part 60, Subpart VV	Does not produce chemicals listed in 60.489 as an intermediate or final product.
GRP-P/PFUG	F-100, F-3.01, F-3.02, F-3.03, F-BULLETTS, F-DEHY	40 CFR Part 63, Subpart HH	Not an oil and natural gas production facility as defined in 63.760(a)(1).
GRP-PHTFUG	PHT-100, PHT-200	30 TAC Chapter 115, HRVOC Fugitive Emissions	Fugitives not associated with a synthetic organic chemical, polymer, resin, or MTBE manufacturing process, or natural gas/gasoline processing operation as defined in §115.10.
GRP-PHTFUG	PHT-100, PHT-200	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Fugitives not associated with a synthetic organic chemical, polymer, resin, or MTBE manufacturing process, or natural gas/gasoline processing operation as defined in §115.10.
GRP-PHTFUG	PHT-100, PHT-200	40 CFR Part 60, Subpart KKK	Not an affected facility as defined in 60.630(a)(2) or (a)(3).
GRP-PHTFUG	PHT-100, PHT-200	40 CFR Part 63, Subpart HH	Not an oil and natural gas production facility as defined in 63.760(a)(1).
GRP-POND	POND-A, POND-B, POND-C, POND-D, POND-E	30 TAC Chapter 115, Industrial Wastewater	Not an affected VOC wastewater stream according to 115.140(2).

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GRP-PTANKS	EPHT-T-1, EPHT-T-1A, EPHT-T-1B, EPHT-T-1C, EPHT-T-2, EPHT-T-2A, EPHT-T-2B, EPHT-T-3B, EPHT-T-3B, EPHT-T-4B, EPHT-T-5A, EPHT-T-5A, EPHT-T-5A, EPHT-T-5B, PP3-T-1006, PP3-T-1006C, PP3-T-1006D, PP3-T-1007, PP3-T-2006E	40 CFR Part 60, Subpart Kb	These are pressure vessels with no emissions to the atmosphere.
GRP-SPENTC	PP3-T-1003, PP3-T-3003	40 CFR Part 60, Subpart Kb	Storage vessel capacity is less than 75 cubic meters (19,812 gallons).
H-1401	N/A	40 CFR Part 60, Subpart Dc	The heat input capacity for the unit is less than 10 MMBtu/hr.
H-1401	N/A	40 CFR Part 63, Subpart JJJJJJ	This unit is not an industrial, commercial, or institutional boiler as defined in 63.11237.
H-1402	N/A	40 CFR Part 60, Subpart Dc	The heat input capacity for the unit is less than 10 MMBtu/hr.
H-1402	N/A	40 CFR Part 63, Subpart JJJJJJ	This unit is not an industrial, commercial, or institutional boiler as defined in 63.11237.
H-2401	N/A	40 CFR Part 60, Subpart Dc	The heat input capacity for the unit is less than 10 MMBtu/hr.
H-2401	N/A	40 CFR Part 63, Subpart JJJJJJ	The unit is not an industrial, commercial, or institutional boiler as defined in §63.11237.
H-3401	N/A	40 CFR Part 63, Subpart JJJJJJ	This unit is not an industrial, commercial, or institutional boiler as defined in 63.11237.
HT15.003	N/A	40 CFR Part 63, Subpart JJJJJJ	This unit is not an industrial, commercial, or institutional boiler as defined in 63.11237.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
PHT-LOAD	N/A	40 CFR Part 60, Subpart XX	Site is not a bulk gasoline terminal.
PHT-LOAD	N/A	40 CFR Part 61, Subpart BB	Site is not a benzene transfer operation.
PHT-LOAD	N/A	40 CFR Part 63, Subpart R	Site is not a bulk gasoline terminal or pipeline breakout station.
REGEN-1	N/A	40 CFR Part 63, Subpart JJJJJJ	This unit is not an industrial, commercial, or institutional boiler as defined in 63.11237.

## **New Source Review Authorization References**

New Source Review Authorization References	48
New Source Review Authorization References by Emission Unit	49

## **New Source Review Authorization References**

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.		
Authorization No.: 93973	Issuance Date: 12/19/2019	
Authorization No.: 109745	Issuance Date: 06/12/2013	
Authorization No.: 139915	Issuance Date: 05/06/2016	
Permits By Rule (30 TAC Chapter 106) for the	Application Area	
Number: 51	Version No./Date: 09/12/1989	
Number: 83	Version No./Date: 09/12/1989	
Number: 83	Version No./Date: 05/04/1994	
Number: 106.183	Version No./Date: 09/04/2000	
Number: 106.261	Version No./Date: 09/04/2000	
Number: 106.261	Version No./Date: 11/01/2003	
Number: 106.263	Version No./Date: 11/01/2001	
Number: 106.371	Version No./Date: 09/04/2000	
Number: 106.472	Version No./Date: 03/14/1997	
Number: 106.472	Version No./Date: 09/04/2000	
Number: 106.476	Version No./Date: 09/04/2000	
Number: 106.478	Version No./Date: 09/04/2000	
Number: 106.492	Version No./Date: 09/04/2000	
Number: 106.511	Version No./Date: 09/04/2000	

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
223A-PPIII	P/P DISTILLATION UNIT NO. 1	93973
223B-PPIII	P/P DISTILLATION UNIT NO. 2	93973
223C-PPIII	P/P DISTILLATION UNIT NO. 3	93973
BRMGEN	EMERGENCY GENERATOR	106.511/09/04/2000
CWT-1	COOLING TOWER	106.371/09/04/2000
D-TANK-1	FIRE WATER DIESEL TANK NO. 1	93973
D-TANK-2	FIRE WATER DIESEL TANK NO. 2	93973
DEGAS-A	BRINE DEGASSER A	93973
DEGAS-B	BRINE DEGASSER B	93973
DEGAS-C	BRINE DEGASSER C	93973
DEGAS-DE	BRINE DEGASSER DE	93973
EPHT-MCAP	MERCAPTAN BULLET TANK	106.476/09/04/2000
EPHT-T-1	P/P MIX STORAGE TANK	106.476/09/04/2000
EPHT-T-1A	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-1B	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-1C	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-2	P/P MIX STORAGE TANK	106.476/09/04/2000
EPHT-T-2A	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-2B	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-3	P/P MIX STORAGE TANK	106.476/09/04/2000
EPHT-T-3A	PROPANE STORAGE TANK	106.476/09/04/2000

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
EPHT-T-3B	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-4A	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-4B	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-5A	PROPANE STORAGE TANK	106.476/09/04/2000
EPHT-T-5B	PROPANE STORAGE TANK	106.476/09/04/2000
EQUIP-D-TANK	EQUIPMENT DIESEL TANK	93973
F-100	UNDERGROUND HYDROCARBON STORAGE FUGITIVES	93973, 106.261/09/04/2000 [140448]
F-3.01	SPLITTER NO. 1 FUGITIVES	93973
F-3.02	SPLITTER NO. 2 FUGITIVES	93973
F-3.03	SPLITTER NO. 3 FUGITIVES	93973, 106.261/09/04/2000 [155109]
F-BULLETTS	NGL HYDROCARBON STORAGE FUGITIVES	93973
F-DEHY	FUGITIVES	106.261/09/04/2000 [154647]
FL-06	EAST FLARE (STORAGE & SLITTER 3 UNIT 3)	93973, 109745, 139915, 106.261/09/04/2000 [155109]
FL-08	EAST FLARE (SLITTER 3 UNIT 1 & 3)	93973
FL-COLD	COLD FLARE	106.492/09/04/2000 [154647]
FTK-13E	FRAC TANK-DIESEL	106.472/09/04/2000
FTK-20E	FRAC TANK-DIESEL	106.478/09/04/2000
FW-1	FIRE WATER PUMP 1	93973
FW-2	FIRE WATER PUMP 2	93973
FWPOND-E	EAST FIRE WATER POND	106.472/09/04/2000

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FWPOND-W	WEST FIRE WATER POND	106.472/09/04/2000
H-1401	MOL SIEVE REGEN HEATER	93973
H-1402	MOL SIEVE REGEN HEATER	93973
H-2401	MOL SIEVE REGEN HEATER	93973
H-3401	MOL SIEVE REGEN HEATER	93973
HT15.003	REBOILER	106.183/09/04/2000 [154647]
PHT-100	EAST PHT AREA 100 FUGITIVES	106.261/11/01/2003 [81822]
PHT-200	EAST PHT AREA 200 FUGITIVES	106.261/11/01/2003 [81822]
PHT-LOAD	EAST PHT TRUCK RACK	106.261/11/01/2003 [81822]
POND-A	BRINE POND A	93973
POND-B	BRINE POND B	93973
POND-C	BRINE POND C	93973
POND-D	BRINE POND D	93973
POND-E	BRINE POND E	93973
PP3-T-1001	RGP CHARGE SPHERE	83/09/12/1989
PP3-T-1003	SPENT CAUSTIC TANK	51/09/12/1989
PP3-T-1004	FRESH CAUSTIC TANK	83/09/12/1989
PP3-T-1006A	PROPYLENE BULLET TANK	83/09/12/1989
PP3-T-1006B	PROPYLENE BULLET TANK	83/09/12/1989
PP3-T-1006C	PROPYLENE BULLET TANK	83/09/12/1989
PP3-T-1006D	PROPYLENE BULLET TANK	83/09/12/1989

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
PP3-T-1007	PROPANE BULLET TANK	83/09/12/1989
PP3-T-2006E	PROPANE STORAGE TANK	83/05/04/1994
PP3-T-3003	SPENT CAUSTIC TANK	106.472/03/14/1997
PP3-T-3004	FRESH CAUSTIC TANK	106.472/03/14/1997
REGEN-1	MOL SIEVE REGEN HEATER	106.183/09/04/2000 [155109]
TK-DGS109	CBOB ADDITIVE TANK	106.472/09/04/2000
TK-FOA3	DIESEL ADDITIVE TANK	106.472/09/04/2000

<sup>\*\*</sup>This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

	Alternative Requirement	
Alternative Requirement		 54

Kathleen Hartnett White, Chairman R. B. "Ralph" Marquez, Commissioner Larry R. Soward, Commissioner Glenn Shankle, Executive Director



## TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

July 27, 2006

Mr. Charles Markowitz Environmental Manager Enterprise Products Operating, L.P. P.O. Box 573 Mont Belvieu, Texas 77580



Re: Request for Monitoring Modifications, Title 30 Texas Administrative Code (30 TAC), Chapter 115, Subchapter H, Highly Reactive Volatile Organic Compounds (HRVOC), Division 2, Enterprise Products Operating L.P. (Enterprise Products).

#### Dear Mr. Markowitz:

This letter is in response to your letter dated June 6, 2006, providing additional information concerning Enterprise Products' request for approval of an alternative sparger for use with continuous HRVOC monitoring systems for monitoring cooling tower heat exchange systems under 30 TAC Chapter 115, Subchapter H, Division 2. Enterprise Products requested approval of the Siemens Model 'Al 2-HRVOC' sparging system as an alternative to the air stripping apparatus specified in Appendix P of the TCEQ Sampling Procedures Manual to satisfy the continuous monitoring requirements in §115.764(a)(6). Enterprise Products provided the comparison test results for validating the Siemens Model 'Al 2-HRVOC' sparging system against the Appendix P system according to U.S. Environmental Protection Agency (EPA) Method 301 as required by 30 TAC§115.764.

TCEO has reviewed Enterprise Products request and the results of the Method 301 comparison test. Based on the information and test data submitted, the Siemens Model "AI 2-HRVOC" sparging system meets all the criteria specified in Method 301 to be considered equivalent to the Appendix P air stripping system for ethylene, propylene, all isomers of butene, and 1,3-butadiene. Therefore, TCEQ approves Enterprise Products request to use of the Siemens Model "AI 2-HRVOC" sparging system for performing cooling tower monitoring of ethylene, propylene, all isomers of butene, and 1,3-butadiene as specified in 30 TAC Chapter 115, Subchapter H, Division 2, §115.764(a)(6). Correction factors for ethylene, propylene, isomers of butene, and 1,3-butadiene must be applied as specified in Method 301. The approval specified in this correspondence is only applicable to continuous monitoring performed as required by 30 TAC Chapter 115, Subchapter H, Division 2, §117.764(a)(6) or (b)(6), and is site-specific to cooling tower heat exchange systems located at the following Enterprise Products facilities:

P.O. Box 13087 • Austin, Texas 78711-3087 • 512/239-1000 • Internet address: www.tceq.state.tx.us

@PFDesktop\::ODMA/GRPWISE/TNRDOM3.DMS3APO.AOPDP95A-New:45335.2

Revised - Effective 02/2008 Page 115

Mr. Charles Markowitz Page 2 July 27, 2006

- Mont Belvieu Facility, Mont Belvieu, Chambers County, Texas Commission on Environmental Quality (TCEQ) Regulated Entity RN102323268;
- East Storage/Splitter III Facility, Mont Belvieu, Chambers County, TCEQ Regulated Entity RN10284911;
- Morgan's Point Facility, La Porte, Harris County, TCEQ Regulated Entity RN100210665;
   and
- Almeda Facility, Houston, Harris County, TCEQ Regulated Entity Number RN102940103;

If you have any questions concerning this correspondence, please contact me at the letterhead address, Mail Code MC-206, by telephone at (512) 239-6041, or by email at <a href="mailto:vmeiller@tceq.state.tx.us">vmeiller@tceq.state.tx.us</a>.

Sincerely,

Whey Forther for Vincent R. Meiller

Air Quality Planning Section

Texas Commission on Environmental Quality

	Appendix A	
Acronym List		57

# **Acronym List**

The following abbreviations or acronyms may be used in this permit:

	actual cubic fact nor minute
	actual cubic feet per minute
	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
	continuous emissions monitoring system
	continuous opacity monitoring system
CVS	closed vent system
D/FW	
	emission point
	U.S. Environmental Protection Agency
	emission unit
EO	
	Federal Clean Air Act Amendments
	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	
	hydrogen sulfide
	identification number
	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
	Million British thermal units per hour nonattainment
NA	nonattainment
NA N/A	nonattainmentnot applicable
NA N/A NADB	nonattainment not applicable National Allowance Data Base
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60)
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit process unit process unit state implementation plan
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit process unit process unit process unit state implementation plan sulfur dioxide
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality